

TURNTABLES QUOTATION WORKSHEET

Company _____ Date _____
Contact _____ Quote Due _____ Desired Delivery _____
Phone No. _____ Contact Email _____ State _____
Omni Sales Contact _____ Quote # _____
Quantity: _____

Product Specs:

Max:

- Width (inches): _____ Length (inches): _____

- Height (inches): _____ Weight (lbs): _____

Min:

- Width (inches): _____ Length (inches): _____

- Height (inches): _____ Weight (lbs): _____

Description: _____

Max. Qty.: _____ Total Live Load: _____

Temperature

-Environment: _____

-Product: _____

Turntable Construction:

- Welded
 - Painted Epoxy Painted
 - Powder Coated Color RAL: _____

Diameter of Table: _____

Top of Table: _____

Top of Roller: _____

Capacity: _____

Bearing Support

- Cam Follower Roller Turn Roller
- Rotary Bearing Yoke Roller

Powered Turntable Specifications:

Rotation:

- 90 Deg. 180 Deg. 270 Deg. 360 Deg.
- Other: _____

Time for Specified Rotation: _____

Method of Drive:

- Sprocket and Chain
- Other: _____

Plant Voltage:

- 110V Single Phase 460V Three Phase
- 220V Single Phase 208V Three Phase
- 220V Three Phase 575V Three Phase

Transition Rollers:

- Gravity Rollers Power Rollers

Approval Drawing Required: Yes No

Manual Turntable Specifications:

Rotation:

- 90 Deg. 180 Deg. 270 Deg. 360 Deg.
- Other: _____

Detents: Yes No

Low Profile Manual Turntable (LPMT) Specifications:

Rotating Deck Size: (Capacity)

(2000#) 24" Square 36" Square 48" Square

(4000#) 24" Square 36" Square 48" Square

(LPMT) Options:

- Detent Stops @ 90 Degrees (Spring) Not Locking
- Detent Hand Release @ 90 Degrees
- Detent Foot Release @ 90 Degrees
- Circular Table Platform Stand
- Cross Bracing (Above 30" T.O.T.)

Note: NOT Recommended for use with conveyor because of offset loading.

Options:

Table Position Sensing: Mounted Only
 Mounted and Wired

Voltage: _____

Limit Switch: _____

Proximity Switch: _____

Slip Ring (Y/N) 8-Pole Standard Mounted and

Wired: _____

(Slip Ring maybe required over 270 degrees)

Notes: _____
